

Performance Characteristics

Operating Voltage: 250VAC max.  
 Current rating: 1Amp max.  
 Contact Resistance: 20 mΩ max.  
 Insulation Resistance: 1000M Ω min. At 500V DC.  
 Dielectric Withstanding Voltage: 600V AC RMS for 1 minute.  
 Durability: 25 cycles no electrical degradation.  
 Operating Temperature: -40° C to +105° C.

Drawing Note: All Dim. Tolerance Are  $\pm 0.25$   
 (Unless Otherwise Noted)

Material

Insulator: Glass reinforced PPS or PBT  
 UL94V-0 rated.

Contact: Phosphor Bronze.

Plating: Tin over Nickel plated,  
 Gold Plating optional.


Color of Insulator: Brown

TABLE OF DIMENSION

NO. OF CONTACTS	A $\pm 0.20$	B $\pm 0.20$	C $\pm 0.20$	D $\pm 0.20$	E $\pm 0.20$
20P	15.56	15.56	5.08	5.08	18.20
28P	18.10	18.10	7.62	7.62	21.70
32P	18.10	20.64	7.62	7.62	23.65
44P	23.18	23.18	12.70	12.70	28.80
52P	25.72	25.72	15.24	15.24	32.50
68P (PPS)	30.80	30.80	20.32	20.32	40.00
68P	31.60	31.60	20.32	20.32	40.00
84P (PPS)	35.88	35.88	25.40	25.40	47.15
84P	36.68	36.68	25.40	25.40	47.15

PLCC SOCKET DIP

Customer:	Approval:	Unit	Scale	Date
Drawing:	Check:	mm		15.04.22



P/NO:  
 Pin Longer:  
 Signaturer:

深圳市永连旺电子有限公司