


(BOTTOM CONTACT TYPE)

- NOTES
1. MATERIALS
COVER:PPS UL94V-0
HOUSING:LCP UL94V-0
CONTACT:PHOSPHOR BRONZE.
 2. FINISH
LATCH:PHOSPHOR BRONZE
 3. SPECIFICATION
CONTACT:1. TIN/LEAD
90/10, 120u"
LATCH:TIN/LEAD
90/10, 120u"
VOLTAGE RATING:50V
CURRENT RATING:50V
CONTACT RESISTANCE:20M
OHM MIN
INSULATION
RESISTANCE:100M OHM MIN
TEMPERATURE RANGE:-20°
TO 85° C.
 4. THIS PRODUCT IS LOWER CONTACT TYPE CONNECTOR. IN THE PACKAGE ACTUATOR SHOULD BE LOCKED.

P. NO	A	B	C	D	E
3P	6.95	1.00	5.85	6.65	2.00
4P	7.45	1.50	6.35	7.15	2.50
5P	7.95	2.00	6.85	7.65	3.00
6P	8.45	2.50	7.35	8.15	3.50
7P	8.95	3.00	7.85	8.65	4.00
8P	9.45	3.50	8.35	9.15	4.50
9P	9.95	4.00	8.85	9.65	5.00
10P	10.45	4.50	9.35	10.15	5.50
11P	10.95	5.00	9.85	10.65	6.00
12P	11.45	5.50	10.35	11.15	6.50
13P	11.95	6.00	10.85	11.65	7.00
14P	12.45	6.50	11.35	12.15	7.50
15P	12.95	7.00	11.85	12.65	8.00
16P	13.45	7.50	12.35	13.15	8.50
17P	13.95	8.00	12.85	13.65	9.00
18P	14.45	8.50	13.35	14.15	9.50
19P	14.95	9.00	13.85	14.65	10.0
20P	15.45	9.50	14.35	15.15	10.5
21P	15.95	10.0	14.85	15.65	11.0
22P	16.45	10.5	15.35	16.15	11.5
23P	16.95	11.0	15.85	16.65	12.0
24P	17.45	11.5	16.35	17.15	12.5
25P	17.95	12.0	16.85	17.65	13.0
26P	18.45	12.5	17.35	18.15	13.5
27P	18.95	13.0	17.85	18.65	14.0
28P	19.30	13.5	17.35	18.05	14.5
29P	19.95	14.0	18.85	19.65	15.0
30P	20.45	14.5	19.35	20.15	15.5
31P	20.95	15.0	19.85	20.65	16.0
32P	21.45	15.5	20.35	21.15	16.5
33P	21.80	15.7	20.85	20.60	17.0
34P	22.45	16.5	21.35	22.15	17.5
35P	22.95	17.0	21.85	22.65	18.0
36P	23.45	17.5	22.35	23.15	18.5
37P	23.95	18.0	22.85	23.65	19.0
38P	24.45	18.5	23.35	24.15	19.5
39P	24.95	19.0	23.85	24.65	20.0
40P	25.70	19.5	24.05	24.45	20.5
41P	25.95	20.0	24.85	25.65	21.0
42P	26.45	20.5	25.35	26.15	21.5
43P	26.95	21.0	25.85	26.65	22.0
44P	27.45	21.5	26.35	27.15	22.5
45P	27.95	22.0	26.85	27.65	23.0
46P	28.45	22.5	27.35	28.15	23.5
47P	28.95	23.0	27.85	28.65	24.0
48P	29.45	23.5	28.35	29.15	24.5
49P	29.95	24.0	28.85	29.65	25.0
50P	30.45	24.5	29.35	30.15	25.5

FPC PITCH0.5mm 下接

Customer:	Approval:	Unit	Scale	Date
Drawing:	Check:	mm		15.08.23



P/NO:
Pin Longger:
Signatuer:

深圳市永连旺电子有限公司